



newline *ip*



Superior
Touch



Ultra
Lightweight



Object
Recognition



Superior
Image Quality



Security



Maximum
Viewing Angle



Optically
Bonded
PCAP



Easy
Installation

UNMATCHED POWERFUL PCAP WITH ENTERPRISE LEVEL SECURITY

IP series is newline's premium solution for the corporate workspace. Based on the combination of optical bonding technology and capacitive touch technology this product line features a superior touch experience, crystal clear images and a true maximum viewing angle. This product line comes in a wide variety of sizes and can be easily combined with the newline 4K wide-angle camera with microphone. This versatile premium solution is optimized for Windows and suits any workspace, from the huddle room to large meeting room.

IP series can ensure enterprise level security. This solution has no functional Android which makes it safer. You can still benefit from the Newline interactive ecosystem. Simply complete your IP series with a newline OPS including the Windows bundle of interactive ecosystem tools for a full newline experience!

IP series is compatible with newline OPS with Newline interactive ecosystem tools for Windows:

CAST

BROADCAST

newline ip

Model	TT-5519IP	TT-6519IP	TT-7519IP	TT-8619IP
Display				
Display Backlight	LED			
Display Area	1211 x 682 mm	1428 x 804 mm	1650 x 928 mm	1895 x 1066 mm
Active Screen Size (inch)	55"	65"	75"	86"
Display Ratio	16 : 9			
Resolution	3840 x 2160 Pixels			
Display Colors	8 bit + FRC (1.07 billion)	8 bit + FRC (1.07 billion)	8 bit + FRC (1.07 billion)	10bit 1.07Billion
LCD Brightness(After Glass)	≥ 370 nit			
Contrast Ratio (Dynamic)	4000:1			
Viewing Angle	178°			
Life time (working hours/day)	50,000 hours			
Response Time	8ms			
Speaker				
Speaker Position	Downward facing			
Transmission Range	5M			
Speaker Max.Power Output	15 W x 2			
Power				
Power Consumption	Maximum ≤350 W Standby Mode ≤ 0.5 W	Maximum ≤350 W Standby Mode ≤ 0.5 W	Maximum ≤ 400 W Standby Mode ≤ 0.5 W	Maximum ≤ 450 W Standby Mode ≤ 0.5 W
Working Voltage	AC100-240V ; 50/60 Hz			
Touch				
Touch Surface Technology	Anti-Glare, tempered glass with Optical bonding			
Touch Surface Hardness	>7H			
Touch Sensor	PCAP			
Touch Points	20 Points			
Touch Screen Writing Tools	Newline passive pen or finger			
Communication Interface	USB-B			
Transportation/ Storage				
Storage Temperature/ Humidity	-10°C~45°C/20~90% RH (No condensation)		-20°C ~ 60°C / 20 ~ 90% RH (No condensation)	
Working Temperature/ Humidity	0°C~40°C/20~80% RH (No condensation)		0°C ~ 45°C / 20 ~ 80% RH (No condensation)	
Mounting Options	Wall-mount or Mobile Stand			
Outline Dimensions	1290 x 764 x 73 mm	1509 x 866 x 86 mm	1731 x 1010 x 86 mm	1977 x 1150 x 86 mm
Packing Dimensions	1417 x 871 x 221 mm	1640 x 1036 x 221 mm	1859 x 1136 x 247 mm	2119 x 1281 x 275 mm
Net Weight	28kg	36kg	49kg	60kg
Gross Weight	36kg	46.5kg	62kg	76kg
Vesa Mount Installation Position	600 x 400 mm	600 x 400 mm	800 x 400 mm	800 x 400 mm
Ports				
Front Interface Inputs	None			
Rear AV Inputs	HDMI 2.0 in x 2, VGA IN x 1, VGA Audio in x 1, YPbPr in x 1, CVBS in x 1, AV (L&R) in x 1			
AV Outputs	AV out x 1, Ear Phone x 1			
Other	USB2.0 x 1, Touch USB (Type B) x 1, RS232 x1, OPS Slot x1(4K@60Hz)			
Embedded Operating System				
CPU	MIPS Advanced Multi-core CPU			
GPU	MStarACE6 Video Processor			
RAM	2GB DDR4 MCP			
ROM	64MB norflash			
External Memory	None			
Android Version	None			
Other				
OPS PC	Optional			
Wi-Fi Dongle	N/A			
Newline Software Content	Newline Cast & Broadcast (Support Windows)			

newline



AV MEDIA PTE LTD

Bk 2023 #02-106, Bukit Batok Industrial Park A St.23, S (659528)
Tel: (65) 6569 2123 Fax: (65) 6569 6589
Email: avm@avmedia.com.sg
Website: www.avmedia.com.sg

newline-interactive.com