

# PTZ-HU2016/V

## FHD Video Conference Camera



### Features

- 20x Optical Zoom + 16x Digital Zoom
- Support HDMI, USB and LAN video output
- Supports 1080p at 60fps
- Able to control via RS232 or RS485
- Support Ceiling-Mount

### Technical specification

#### Camera

Sensor	1/2.7" 2.07MP CMOS
Optical Zoom	20x, f = 4.42mm - 88.5mm
Digital Zoom	16x
Aperture	F = 1.8 ~ 2.8
Minimal Illumination	0.5 Lux @ (F1.8)
Viewing Angle	60.7°(H) / 34.1° (V)
Video S/N Ratio	≥ 55dB
White Balance	Auto / Manual
Local Storage	Yes
Number of preset	255
Panning Angle	-170° + 170°
Panning Speed	1.7°- 100°/sec
Tilting Angle	-30° + 90°
Tilting Speed	1.7° - 69.9°/sec

#### Interface

Video Output Interface	1 x HDMI (Version 1.3), 1 x USB 3.0, 1 x USB 2.0, 1 x LAN
Video Format	1080p/60, 1080p/30, 1080p/25, 720p/60, 720p/50
Audio Interface	1 x 3.5mm Audio Input (Line in)
Camera Control Interface	1 x RS232 In, 1 x RS485, 1 x RS232 Out
Control Protocol	VISCA / Pelco-D / Pelco-P

#### Network

IP Video Compression	H.265 / H.264 / MJPEG
IP Video Stream	Main Stream, Sub Stream
Network Protocols	RTSP, RTMP, ONVIF

#### Other Parameters

Operating Temperature	-10°C to 40°C
Power Consumption	12W (Max)
Power Supply	12V DC In, 1A
Dimension	169mm x 142mm x 164mm
Weight	1.35 Kg