

Two-way All-weather Speaker



6" Weatherized
Passive Speaker
Model: **LT206, LT206T**



8" Weatherized
Passive Speaker
Model: **LT208, LT208T**



12" Weatherized
Passive Speaker
Model: **LT212, LT212T**



15" Weatherized
Passive Speaker
Model: **LT215, LT215T**

Models	LT206 LT206T	LT208 LT208T	LT212 LT212T	LT215 LT215T
Speaker Unit	LF: 1 x 6.5"/1.4" HF: 1 x 0.8"/1"	LF: 1 x 8"/2" HF: 1 x 1"/1.4"	LF: 1 x 12"/3" HF: 1 x 1"/1.7"	LF: 1 x 15"/3" HF: 1 x 1.4"/3"
Rated Impedance	8Ω	8Ω	8Ω	8Ω
Rated Power (RMS)	LT206: 100W LT206T: 25W/50W/100W/OFF	LT208: 150W LT208T: 37.5W/75W/150W/OFF	LT212: 300W LT212T: 50W/100W/200W/OFF	LT215: 400W LT215T: 75W/150W/300W/OFF
Frequency Response (-3dB)	-	80Hz - 18KHz	55Hz - 18KHz	50Hz - 18KHz
Frequency Response (-10dB)	100Hz - 18KHz	75Hz - 20KHz	50Hz - 20KHz	45Hz - 20KHz
Directivity (H*V)	100° x 100°	80° x 80°	70° x 50°	60° x 40°
Max SPL	113dB (continuous) 119dB (peak)	118dB (continuous) 124dB (peak)	123dB (continuous) 129dB (peak)	129dB (continuous) 135dB (peak)
Material	Polymer			

* Model T is Weatherized Passive Speaker w/ Transformer